



## FULL SYNTHETIC PASSENGER CAR MOTOR OIL

**PERFORMANCE PLUS<sup>®</sup> Full Synthetic Passenger Car Motor Oils** are specially formulated with high-quality Group III base oil plus state-of-the art performance additives. They are engineered to meet or exceed the demands of turbocharged, high powered, high-efficiency, gasoline and propane engines in the latest model passenger cars and light duty trucks.

### TYPICAL PROPERTIES

PERFORMANCE PLUS <sup>®</sup>	SAE	0W-20	5W-20	5W-30	10W-30	5W-40
API Service		SN	SN	SN	SN	SN
ILSAC		GF-5	GF-5	GF-5	GF-5	-
Kinematic Viscosity						
cSt @ 40°C		46.3	48.7	62.7	67.3	90.5
cSt @ 100°C		8.7	8.6	10.8	10.5	14.7
Viscosity Index		169	157	164	144	170
CCS Viscosity						
cP @ -35°C		5600	-	-	-	-
cP @ -30°C		-	4600	5000	-	6000
cP @ -25°C		-	-	-	5200	-
Evaporative Loss, NOACK, wt%		< 15	< 15	< 15	< 15	< 15
Specific Gravity 15.6°C (60°F)		0.846	0.850	0.850	0.856	0.852
Flash Point, °C		210	208	204	204	208
Pour Point, °C		-51	-48	-48	-42	-45
Color (ASTM)		3.0	3.0	3.0	3.0	3.0
Sulfated Ash, wt%		0.92	0.92	0.92	0.92	0.92

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. 01/16