



## HEAVY DUTY DIESEL SYNTHETIC BLEND 15W-40 CJ-4/SN

**PERFORMANCE PLUS® Heavy Duty Diesel Synthetic Blend 15W-40 Engine Oil** is specifically engineered to meet the latest requirements for EGR / EPF engines. Meets or exceeds API Service CJ-4 / SN as well as older API categories CI-4 Plus, and CI-4. 15W-40 meets or exceeds Mack EO-O Premium Plus, Cummins CES 20081, Detroit Diesel PGOS 93K218 and Volvo VDS-4, Caterpillar ECF-1A, 2 and 3, MB 228.3, ACEA E-9 2012, Komatsu Tier 4i, and MTU Type II standards for performance and protection. Recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline, or propane engines.

This product is formulated with Group III base oils and Kleen Performance Products' hydro-treated, high VI, Group II+ base oils.

TYPICAL PROPERTIES	
PERFORMANCE PLUS SAE	15W-40
API Service	CJ-4/SN
Kinematic Viscosity cSt @ 40°C cSt @ 100°C	113.9 15.5
Viscosity Index	143
CCS Viscosity cP @ -20°C	5300
Flash Point, °C	236
Pour Point, °C	-36
Specific Gravity 15.6°C (60°F)	0.865
Color (ASTM)	L 4.0
TBN	9.6
Sulfated Ash, wt%	0.98

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. 6/16