



HIGH MILEAGE PASSENGER CAR MOTOR OILS

PERFORMANCE PLUS[®] High Mileage Motor Oil for passenger cars provides maximum protection for longer engine life in vehicles with over 75,000 miles. The formulation contains extra additives to help stop leaks and reduce oil consumption by conditioning seals and gaskets. Plus, it reduces sludge and damaging deposits.

Performance Plus[®] High Mileage Motor Oils are specially formulated with Group II+ base oils plus state-of-the art performance additives and are engineered to exceed the demands of turbocharged and high-power, high-efficiency gasoline, propane, and natural gas engines in the latest model passenger cars and light duty trucks. SAE 5W-20, 5W-30, and 10W-30 grades are Resource Conserving motor oils that exceed API service SN and ILSAC Starburst GF-5, as well as older service categories SM, SL, and previous ILSAC categories.

The foundation of Performance Plus Oils are Kleen Performance Products' hydro-treated, high VI, Group II+ base oils.

TYPICAL PROPERTIES

PERFORMANCE PLUS [®]	SAE	5W-20	5W-30	10W-30
API Service		SN	SN	SN
ILSAC		GF-5	GF-5	GF-5
Kinematic Viscosity				
cSt @ 40°C		49.9	62.8	70.9
cSt @ 100°C		8.6	10.5	10.8
Viscosity Index		151	158	142
CCS Viscosity				
cSt @ -30°C		6000	6200	-
cSt @ -25°C		-	-	6200
Evaporative Loss, NOACK, wt%		< 15	< 15	< 15
Specific Gravity @ 15°C (60°F)		0.861	0.861	0.867
Flash Point, °C		222	224	232
Pour Point, °C		-39	-39	-39
Color (ASTM)		L 3.0	L 3.0	L 3.0

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. 7/16