



SYNTHETIC BLEND PASSENGER CAR MOTOR OIL

PERFORMANCE PLUS[®] Synthetic Blend Passenger Car Motor Oils are specially formulated with a combination of Group II+ and Group III base oils plus state-of-the art performance additives and are engineered to exceed the demands of turbocharged and high-power, high-efficiency gasoline, propane, and natural gas engines in the latest model passenger cars and light duty trucks. SAE 5W-20 and 5W-30 grades are Resource Conserving motor oils that exceed API service SN and ILSAC Starburst GF-5, as well as older service categories SM, SL, and previous ILSAC categories.

The foundation of Performance Plus Oils are Kleen Performance Products' hydro-treated, high VI, Group II+ base oils.

TYPICAL PROPERTIES				
PERFORMANCE PLUS [®]	SAE	5W-20	5W-30	10W-30
API Service		SN	SN	SN
ILSAC		GF-5	GF-5	GF-5
Kinematic Viscosity				
cSt @ 100°C		8.8	10.9	10.1
cSt @ 40°C		51.6	65.7	65.1
Viscosity Index		150	158	141
CCS Viscosity				
cP @ -30°C		6000	6200	-
cP @ -25°C		-	-	5100
Evaporative Loss, NOACK, wt%		< 15	< 15	< 15
Specific Gravity @ 15°C (60°F)		0.858	0.860	0.861
Flash Point, °C		220	220	220
Pour Point, °C		-44	-44	-40
Color (ASTM)		3.0	3.0	3.0
Sulfated Ash, wt%		0.92	0.92	0.92

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. 06/15