



## dexos1™ FULL SYNTHETIC PASSENGER CAR MOTOR OIL

PERFORMANCE PLUS® dexos1™ Full Synthetic Passenger Car Motor Oil are approved and licensed to meet GM's stringent requirements for dexos1™ passenger car engine oils.

They are specially formulated with a combination of Group III base oils plus state-of-the art performance additives. And they are engineered to meet or exceed the demands of all engines that specify GM dexos™ approved 0W-20, 5W-20, and 5W-30 engine oils. They also meet or exceed the requirements of Resource Conserving engine oils for API service SN and ILSAC Starburst GF-5, as well as older service categories SM, SL and previous ILSAC categories.

### TYPICAL PROPERTIES

dexos1™ FULL SYNTHETIC	SAE	0W-20	5W-20	5W-30
GM Approved		dexos1™	dexos1™	dexos1™
API Service		SN	SN	SN
ILSAC		GF-5	GF-5	GF-5
Kinematic Viscosity				
cSt @ 100°C		8.4	8.5	11.0
cSt @ 40°C		44.8	48.3	63.9
Viscosity Index		167	154	165
CCS Viscosity				
cP @ -35°C		5600	-	-
cP @ -30°C		-	4800	4900
MRV Viscosity				
cP @ -40°C		< 40000	-	-
cP @ -35°C		-	< 40000	< 40000
Evaporative Loss, NOACK, wt%		< 13	< 13	< 13
Specific Gravity @ 15°C (60°F)		0.846	0.850	0.849
Flash Point, °C		230	230	232
Pour Point, °C		-42	-39	-36
Color (ASTM)		3.0	3.0	3.0
Sulfated Ash, wt%		< 1.0	< 1.0	< 1.0

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. 8/15