



**EcoPower® NGP 15W-40 NATURAL GAS ENGINE OIL** is specially formulated to satisfy the requirements of heavy-duty natural gas engines. It is formally approved for use in natural gas engines with OEM specification Cummins CES 20074.

EcoPower® Heavy Duty Engine Oils provide maximum protection for longer engine life. EcoPower's robust formulation includes:

- **Highest quality re-refined Group II+ base oils** with exceptional purity and lubricating properties that heavy-duty applications demand.
- **State-of-the-art performance additives** including viscosity index improvers, detergents, dispersants, and anti-wear agents provide maximum protection against breakdown and engine wear
  - Unmatched varnish, sludge and carbon deposit control
  - Low valve train, ring and linear wear
  - Extra protection against bearing and bushing corrosion
  - Boosted oxidation control to minimize oil thickening
  - Excellent high-temperature stability
  - Controls oil thickening and provides good filterability with newer, high soot producing, emission-controlled engines
- **EcoPower Engine Oil is beneficial for the environment:**
  - Conserves valuable, non-renewable resources
  - Takes up to 85% less energy to produce than oils made from crude according to recent Dept. of Energy study
  - Reduces greenhouse gas emissions up to 80%

TYPICAL PROPERTIES		
ECOPOWER®	SAE	15W-40
Kinematic Viscosity cSt @ 40°C cSt @ 100°C		104.5 14.5
Viscosity Index		143
CCS Viscosity cP @ -20°C		4900
Flash Point, °C		240
Pour Point, °C		-39
Color (ASTM)		L 3.0
Specific Gravity 15.6°C (60°F)		0.867
TBN		5.9
TAN		1.9
Sulfated Ash, wt%		0.59

Note: Values shown above are representative of current production and may vary within modest ranges Rev. 11/16