



AUTOMATIC TRANSMISSION FLUID

ECOPOWER® Automatic Transmission Fluid is formulated to reduce wear, protect against corrosion, and last longer in vehicles with automatic and power-shift transmissions. It is recommended for domestic and imported transmissions that specify DEXRON®III, DEXRON®IIE, DEXRON®, MERCON®, Ford ESP-M2C138-CJ, Ford ESP-M2C166-H or Type A Suffix A, Allison C-3/C-4, or Caterpillar TO-2 fluids.

Since ECOPOWER® is made from recycled and re-refined used motor oil, it satisfies recent Federal directives for government agencies to use recycled/recovered materials, including:

- Executive Order 13423, signed in 2007 by President Bush, mandates “in Federal agency acquisitions of goods and services use of sustainable environmental practices, including acquisition of bio-based, environmentally preferable, energy-efficient, water-efficient, and recycled-content products”
- Section 6002 of RCRA that requires federal agencies to “procure such items composed of the highest percentage of recovered materials practicable”
- Federal Regulation 23.4 that requires Federal Agencies to “use recovered materials to the maximum extent practicable”

TYPICAL PROPERTIES	
ECOPOWER®	ATF
Specific Gravity 15.6°C (60°F)	0.862
Kinematic Viscosity	
cSt @ 40°C	32.9
cSt @ 100°C	7.0
Viscosity Index	180
Brookfield Viscosity	
cP @ -40°C	17700
Flash Point, °C	204
Pour Point, °C	-51
Color	Red

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. 10/15

DEXRON® is a registered trademark of General Motors Corp. MERCON® is a registered trademark of Ford Motor Company.