



**EcoPower® High Mileage Motor Oil for passenger cars** provides maximum protection for longer engine life in vehicles with over 75,000 miles. The formulation contains extra additives to help stop leaks and reduce oil consumption by conditioning seals and gaskets. Plus, it reduces sludge and damaging deposits. EcoPower's robust formulation includes:

- **Highest quality re-refined Group II+ base oils** with exceptional purity and lubricating properties that are as good or better than base oils made from crude oil
- **State-of-the-art performance additives** including viscosity index improvers, detergents, dispersants, and anti-wear agents provide maximum protection against breakdown and engine wear

**EcoPower Motor Oils**, like the leading motor oils, exceed the toughest North American standards for performance, protection and resource conservation including API service SN and ILSAC GF-5.

Re-refined motor oils, like **EcoPower Motor Oil**, are highly beneficial for the environment:

- Conserves valuable, non-renewable resources
- Takes up to 85% less energy to produce than oils made from crude according to a recent Dept. of Energy study
- Reduces greenhouse gas emissions by over 80%

TYPICAL PROPERTIES			
EcoPower	SAE	5W-20	5W-30
API Service		SN	SN
ILSAC		GF-5	GF-5
Kinematic Viscosity			
cSt @ 40°C		50.0	62.9
cSt @ 100°C		8.6	10.5
Viscosity Index		151	158
CCS Viscosity			
cP @ -30°C		5900	6100
cP @ -25°C		-	-
Evaporative Loss, NOACK, wt%		< 15	< 15
Specific Gravity @ 15°C		0.861	0.861
Flash Point, °C		222	222
Pour Point, °C		-42	-42
Color (ASTM)		L 3.0	L 3.0

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. 06/15