



**EcoPower® Passenger Car Motor Oils** provide maximum protection for longer engine life.

EcoPower's robust formulation includes:

- **Highest quality re-refined Group II+ base oils** with exceptional purity and lubricating properties that are as good or better than base oils made from crude oil
- **Advanced synthetic Group III base oils** for an extra measure of performance and protection under the most severe operating conditions
- **State-of-the-art performance additives** including viscosity index improvers, detergents, dispersants, and anti-wear agents provide maximum protection against breakdown and engine wear

**EcoPower Motor Oils**, like the leading motor oils, exceed the toughest North American standards for performance, protection and resource conservation including API service SN and ILSAC GF-5.

Re-refined motor oils, like **EcoPower Motor Oil**, are highly beneficial for the environment:

- Conserves valuable, non-renewable resources
- Takes up to 85% less energy to produce than oils made from crude according to a recent Dept. of Energy study
- Reduces greenhouse gas emissions by over 80%

### TYPICAL PROPERTIES

EcoPower	SAE	5W-20	5W-30	10W-30
API Service		SN	SN	SN
ILSAC		GF-5	GF-5	GF-5
Kinematic Viscosity				
cSt @ 40°C		50.0	61.7	67.2
cSt @ 100°C		8.7	10.5	10.5
Viscosity Index		151	159	145
CCS Viscosity				
cP @ -30°C		6000	6300	-
cP @ -25°C		-	-	6100
Evaporative Loss, NOACK, wt%		< 15	< 15	< 15
Specific Gravity @ 15°C		0.861	0.860	0.867
Flash Point, C		218	224	236
Pour Point, C		-42	-42	-39
Color (ASTM)		L 3.0	L 3.0	3.0
Sulfated Ash, wt%		0.92	0.92	0.92

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. 06/15