



UNIVERSAL TRACTOR FLUID

ECOPOWER® Universal Tractor Fluid is a premium transmission / differential / hydraulic fluid with superior anti-wear properties recommended for use in powershift / hydrostatic / manual transmissions, differentials, final drives, wet brakes / clutches, power steering, and PTO drives commonly used in farm and construction equipment, off-highway vehicles, and industrial tractors. Some applications include: Power shift transmissions specifying Allison C-3/C-4 or CAT TO-2 fluids; John Deere J20A, J20C; Ford New Holland M2C -41B, -48B, -48C, -86C, -134D; Kubota B6 (UDT); and Vickers 35VQ25.

Since ECOPOWER® is made from recycled and re-refined used motor oil, it satisfies recent Federal directives for government agencies to use recycled/recovered materials, including:

- Executive Order 13423, signed in 2007 by President Bush, mandates “in Federal agency acquisitions of goods and services use of sustainable environmental practices, including acquisition of bio-based, environmentally preferable, energy-efficient, water-efficient, and recycled-content products”
- Section 6002 of RCRA that requires federal agencies to “procure such items composed of the highest percentage of recovered materials practicable”
- Federal Regulation 23.4 that requires Federal Agencies to “use recovered materials to the maximum extent practicable”

TYPICAL PROPERTIES

ECOPOWER®	UTF
Specific Gravity 15.6°C (60°F)	0.869
Kinematic Viscosity cSt @ 40°C	58.7
cSt @ 100°C	9.4
Viscosity Index	140
Brookfield Viscosity cP @ -17°C	2600
Flash Point, °C	226
Pour Point, °C	-42
Color	L 3.0

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. 10/15