



# Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

## EP INDUSTRIAL GEAR OIL

**PERFORMANCE PLUS™ EP Industrial Gear Oils** are specifically formulated to hold up under extreme high pressure in all types of gear sets excluding built-in variable speed friction drives. Approved for use in Chrysler and General Motors. Increase the life of your heavily loaded or shock loaded bearings and gear sets with EP Industrial Gear Oils.

The foundation of Performance Plus Oils are Kleen Performance Products' hydro-treated, high VI base oils.

### PERFORMANCE PLUS PROPERTIES

ISO Viscosity Grade	68	100	150	220	320	460
AGMA Grade	2EP	3EP	4EP	5EP	6EP	7EP
Color	L 3.0	L 3.5	L 3.5	L 3.5	L 4.0	L 5.5
Specific Gravity 15.6°C (60°F)	0.872	0.875	0.881	0.885	0.888	0.892
Kinematic Viscosity						
cSt @ 40°C	66.2	100.5	152.0	221.6	320.0	460.0
cSt @ 100°C	8.9	11.8	15.4	19.5	28.0	30.0
Viscosity Index	109	106	102	100	99	95
Flash Point, °C	233	238	242	246	248	252
Pour Point, °C	-42	-39	-36	-33	-21	-12
Demulsibility D1401	Pass	Pass	Pass	Pass	Pass	Pass
Timken OK Load, lbs	65	65	65	65	65	65
FZG Pass Stage	12	12	12	12	12	12
Copper Corrosion	1B	1B	1B	1B	1B	1B

**For additional qualifications, please contact your Performance Plus Products Sales Representative.**

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 05/17