



**EcoPower® Heavy Duty Diesel 10W-30 FA-4 Engine Oil** is specifically engineered to meet the latest requirements for EGR / EPF engines. 10W-30 FA-4 is a low viscosity product specifically designed to deliver additional fuel economy in newer model year engines. 10W-30 meets or exceeds API Service FA-4 with OEM approvals for Cummins CES 20087 and Detroit Diesel DFS 93K223. As always the customers should follow OEM recommendations.

EcoPower® Heavy Duty Diesel Engine Oils provide maximum protection for longer engine life.

EcoPower's robust formulation includes:

- **Highest quality re-refined Group II+ base oils** with exceptional purity and lubricating properties that heavy-duty applications demand.
- **State-of-the-art performance additives** including viscosity index improvers, detergents, dispersants, and anti-wear agents provide maximum protection against breakdown and engine wear
  - Unmatched varnish, sludge and carbon Deposit control
  - Low valve train, ring and linear wear
  - Extra protection against bearing and bushing corrosion
  - Boosted oxidation control to minimize oil thickening
  - Excellent high-temperature stability
  - Controls oil thickening and provides good filterability with newer, high soot producing, emission-controlled engines
- **EcoPower Engine Oil is beneficial for the environment:**
  - Conserves valuable, non-renewable resources
  - Takes up to 85% less energy to produce than oils made from crude according to recent Dept. of Energy study
  - Reduces greenhouse gas emissions up to 80%

TYPICAL PROPERTIES		
ECOPOWER®	SAE	10W-30
API Service		FA-4
Kinematic Viscosity cSt @ 40°C cSt @ 100°C		66.3 10.2
Viscosity Index		140
CCS Viscosity cP @ -20°C		5,400
Flash Point, °C		237
Pour Point, °C		-39
Specific Gravity @ 60°F		0.86
Color (ASTM)		L 4.0
TBN		10.0
Sulfated Ash, wt%		1.0

Note: Values shown above are representative of current production and may vary within modest ranges  
Rev. 11/16